

Staying Cool: the Thermoelectric Cooling of SiPMs

Julien Hacot-Slonosky

Supervisor: Thomas Brunner

CASST 2024

Contact: julien.hacot-slonosky@mail.mcgill.ca




McGill
UNIVERSITY

Hacot-Slonosky, McGill, Thermoelectric Cooling of SiPMs, CASST 2024



The nEXO Experiment

- A proposed search for the hypothetical neutrinoless double beta decay ($0\nu\beta\beta$), proposed to be at SNOLAB
 - 5 tonnes LXe enriched to 90% ^{136}Xe
 - The time projection chamber houses $\sim 10^4$ silicon photomultipliers (SiPMs) to detect scintillation light from $0\nu\beta\beta$
- Projected half-life sensitivity of 1.35×10^{28} years at 90% C.L.
- Characterize how silicon photomultipliers (SiPMs) act at LXe temperatures



<https://nexo.lnl.gov/nexo-overview>

SiPM Characterization at Low Temperatures

- Silicon photomultipliers (SiPMs) in nEXO will work to detect scintillation light from $\beta\beta$ decay events at LXe temperatures ($\sim -100^\circ\text{C}$).
- One part of testing SiPMs is measuring their sensitivity to a single photon at low temperatures, and so we want to suppress the dark count rate.
- -40°C is a low enough temperature where the dark counts can be neglected.
- Can reach -40°C much more easily with thermoelectric coolers (TECs).


How Do Thermoelectric Coolers Work?

- TEC employ the Peltier effect:
 - When current passes through two dissimilar semiconductors (n-type and p-type), a temperature gradient forms across the junctions, depending on the direction of the current.
- TE coolers pass direct current from N-type to P-type semiconductors.
- Modules are made of many semiconductors arranged thermally in parallel, but electrically in series.

How do TECs Work?



- Modules are made of many semiconductors arranged thermally in parallel, but electrically in series.

Direction of heat moved



Initial Tests

- 1 TEC pressed between a pc chip water cooling block and an aluminum thermal load.
- Closed loop cooling





PC water cooling block

Hacot-Slonosky, McGill, Thermoelectric Cooling of SiPMs, CASST 2024

Initial Tests

- The original setup works:
 - As the water temperature increased, so did the temperature of the aluminum block.
 - Recycled water from closed loop decreases the amount of heat able to be pulled away.
 - Single unit gave a constant $\Delta T \sim 30^\circ\text{C}$.




Upgrading the System

- Two avenues for improvement:
 1. Better heat sink
 - Closed loop recycles warm water with limited heat dissipation
 - Open loop from the building chilled water supply allows for cooler water at constant temperature
 2. More heat moved
 - Using more units allows for greater ΔT
 - Stacking units loses efficiency quickly

The Trouble With Stacking TECs

- The thermal load on an individual TEC increases the further down the stack it is until it cannot cool the load any further.



The Trouble With Stacking TECs

$$\Delta T = 37^\circ\text{C} \quad 8\text{V} \times 3\text{A} = 24\text{W used}$$

For first unit 24 W used + 13 W pumped = 37 W total


$$\Delta T = 3^\circ\text{C} \quad 6\text{V} \times 3\text{A} = 18\text{W used}$$

For second unit 18 W used + 13 W pumped = 31 W total


In total, 18 W used + 21 W used = 39W total for a $\Delta T = 40^\circ\text{C}$

Quickly diminishing returns

Hacot-Slonosky, McGill, Thermoelectric Cooling of SiPMs, CASST 2024




Standard Performance





How to Stack TECs

- 3-stack
 - All thermally in series
 - First two electrically in series
 - Bottom in parallel with first two
- Bottom receives twice the current to deal with the extra heat load



First Trials


- Tested a 3-stack with open loop cooling with water from the tap



Clearly something is not working as intended...


Back to Basics

- The 3-stack method only works if all the units are the same, these were not...
- Replaced the 3-stack with one TEC_{1-12704k10} unit
- Replaced the stainless steel bolts with plastic bolts
- Used open loop water cooling



Back to Basics



Single TEC1-12704, Open Loop



- The open loop cooling is much better than the closed loop cooling
- Using a thermally insulating layer between the hot and cold side also improves performance

Latest Attempt With 3-Stack

- Stacked 3 TEC1-12704k10
- Used 3D printed spacers between the bolts
- Used open loop cooling



Still only -11°C with the 3-stack

Moving Forwards

- Find better ways to thermally isolate the load from the environment, hot side
- Prevent the buildup of ice crystals that will envelop the SiPM
- Incorporate the open loop cooling with the building chilled water supply

Acknowledgements



McGill
UNIVERSITY



Arthur B. McDonald
Canadian Astroparticle Physics Research Institute

Professor Thomas Brunner
And all the McGill Physics
department technical staff



Extra Slides

The Trouble With Stacking TECs

Laird Thermal Systems,
Multistage series electric
cooler

<https://www.lairdthermal.com/datasheets/datasheet-MS2-049-14-14-15-15-11-W8.pdf>

